

A-2030 WET HORIZONTAL UNIT



GENERAL DESCRIPTION

The Magnaflux[®] A-2030 is one of our most economical standard wet bench units. It offers great part mobility for finding surface defects using AC magnetization.

BENEFITS

- Shot time can be adjusted to meet different inspection requirements or needs
- Footswitch to free-up hands for inspection

EXTERIOR

- NEW Touch Screen Interface with standard and optional features. New standard features include:
 - Current Type Selector
 - Adjustable Mag Shot Timer
 - Double Mag Shot
- Innovative pump system for fluid delivery, agitation with easy maintenance access
- Push bar design for easy activation
- Current assurance indicator for magnetic current flow
- Large, easy to read Digital Ammeter
- Independent Contact and Coil Current Controls
- 12 inch (30 cm) diameter coil
- Footswitch-activated pneumatic headstock
- Adjustable tailstock with crank
- Stainless steel tank
- Front and rear maple hardwood grilles

INTERIOR

- Microprocessor control advanced technology; reduce components and increase reliability
- Solid state circuitry
- Liquid Resistant panels, allow ventilation while inhibiting fluid intrusion

SPECIFICATIONS

- 3000 amp AC magnetizing current capability at contacts
- Demag—One Touch decaying AC
- Duty cycle 0.5 seconds on, 10 seconds off (5% with maximum of 2 seconds)
- Off time between magnetizing shots increases for shot time set above 0.5 seconds to maintain 5% duty cycle
- 54 inch (137 cm) headstock/tailstock capacity
- Infinitely variable current control
- Available Voltages: 230, 380, 415, 460, 575, 50 or 60 hertz, single phase power
- Recommended 20 Gallon (75 Liter) Tank Fluid Capacity
- Minimum 80 PSI with 5 SCFM capability
- 89" (224 cm) x 41" (104 cm) Foot Print, allow 24" (61 cm) per side for ventilation

OPTIONAL FEATURES

- 16" coil (41 cm) w/raising block up-grade (In lieu of 12" coil)
- Rotating Contacts (70 lb. Part Capacity; N/A w/12" coil or Auto-Bath; reduces part capacity by 9")
- NRTL Certification to CSA C22.2 No. 61010-1
- Dual Palm Button
- Auto-Bath
 - Automatically applies magnetic particle bath to the part
 - Engage/Disengage switch
 - Adjustable stroke length up to 22 inches
 - Automatic mag shot after Auto-Bath
 - Automatic bath shut off, no flow when bath in retracted position
 - Articulating spray nozzles
- Auto-Mag
 - Automatically clamps part, initiates magnetizing shot, then unclamps part
- Pneumatic Tailstock
 - Lever for operator to push which moves the tailstock up and down the rail
 - Ratchet to manually lock down once in final position
- Configure Unit for 102" Part
 - Recommended 32 Gallon (122 Liter) Tank Fluid Capacity
 - 36" (346 cm) x 41" (104 cm) Foot Print, allow 24" (61 cm) per side for ventilation
- Configure Unit for 146" Part
 - Recommended 55 Gallon (209 Liter) Tank Fluid Capacity
 - 80" (458 cm) x 41" (104 cm) Foot Print, allow 24" (61 cm) per side for ventilation

MATERIALS START UP KIT

Please Choose Water Bath or Oil Bath Start-Up Kit

- Centrifuge Tube, 100 ml, 0-1.0 ml in 0.05 ml increments (Part Number 8493)
- Centrifuge Tube Aluminum Stand (Part Number 1837A)
- Field Indicator (Part Number 2480)
- Two Double-Braided Copper Pads with V- Blocks (Part Number 18948)
- Pie Field Indicator (Part Number 169799)
- UV Filtering Safety Glasses - non tinted (Part Number 506249)

For Oil Baths (Part Number 621452)

- Carrier II oil vehicle, 55 gallon drum
- 14A wet method magnetic particles, 1 lb. bottle

For Water Baths (Part Number 621453)

- 14A Redi-Bath, 6 - 27 oz. bottles for Water Baths

UNIT COMPARISON CHART

AD-2045

4,000 amps AC or 5,000 amps FWDC - 54" (137 cm)
 2 Outputs - Contacts, 12" ID Coil
 Voltages Available (230V or Higher)
 Standard Coil May be Substituted for 16" or 20" ID Coil

ADH-2045

4,000 amps AC or 5,000 amps HWDC - 54" (137 cm)
 2 Outputs - Contacts, 12" ID Coil
 Voltages Available (230V or Higher)
 Standard Coil May be Substituted for 16" or 20" ID Coil

A-2030

3,000 amp AC - 54" (137 cm)
 2 Outputs - Contacts, 12" ID Coil
 Voltages Available (230V or Higher)
 Standard Coil May be Substituted for 16" or 20" ID Coil

SIZE COMPARISON CHART

UNIT SIZE	PART LENGTH CAPACITY	DIMENSIONS	TANK CAPACITY
Standard	54 Inches (137 cm)	89" x 41" x 61"	20 Gal (75L)
Long	102 Inches (259 cm)	136" x 41" x 61"	32 Gal (122L)
Extra Long	146 Inches (371 cm)	180" x 41" x 61"	55 Gal (209L)